

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : <b>H04M 1/72</b>	<b>A1</b>	(11) International Publication Number: <b>WO 99/31860</b>
		(43) International Publication Date: 24 June 1999 (24.06.99)
(21) International Application Number: PCT/US98/18106 (22) International Filing Date: 1 September 1998 (01.09.98) (30) Priority Data: 60/069,552 12 December 1997 (12.12.97) US (71) Applicant (for all designated States except US): THOMSON CONSUMER ELECTRONICS, INC. [US/US]; 10330 North Meridian Street, Indianapolis, IN 46290-1024 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): RAMASWAMY, Kumar [IN/US]; 9417 College Drive #B, Indianapolis, IN 46240 (US). KNUTSON, Paul, Gothard [US/US]; 148 South Emerson Avenue, Indianapolis, IN 46219 (US). (74) Agents: TRIPOLI, Joseph, S. et al.; GE & RCA Licensing Management Operation, Inc., P.O. Box 5312, Princeton, NJ 08540 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  Published With international search report.

(54) Title: BATTERY-BACKUP MECHANISM FOR BASE UNIT OF WIRELESS TELEPHONE SYSTEM



BEST AVAILABLE COPY

(57) Abstract

A wireless telephone system comprises one or more wireless handsets and a base unit. Each handset has a handset transceiver and a rechargeable handset battery for powering the handset. The base unit has a base transceiver for communicating over an RF channel with each handset via its handset transceiver; a recharge cradle for physically docking a docked handset battery comprising one of a detached handset battery and a handset; and a recharge unit for recharging the docked handset battery. The base unit is coupled to an AC power supply and utilizes the docked handset battery as a backup power supply if AC power from the AC power supply is lost or irregular to prevent communication between the base unit and the handsets from being disrupted.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## **BATTERY-BACKUP MECHANISM FOR BASE UNIT OF WIRELESS TELEPHONE SYSTEM**

5

### **BACKGROUND OF THE INVENTION**

#### **Field of the Invention**

The present invention relates to multi-line wireless telephone systems and, in particular, to techniques for ensuring communications despite power losses and irregularities.

#### 10 **Description of the Related Art**

The use of telephones and telephone systems, including wireless telephone systems, is widespread. In wireless telephone systems, one or more cordless or wireless telephone handset units communicate via either analog or digital radio signals with a base unit, which is typically connected via a standard telephone line to an external telephone network. In this manner, a user may employ the wireless handset to engage in a telephone call with another user through the base unit and the telephone network.

Multi-line wireless telephone systems are also in use in various situations, such as businesses with many telephone users. Such systems employ a handset that communicates with up to N handsets simultaneously, typically with digital communications schemes, such as a spread-spectrum, time division multiple access (TDMA). In a TDMA system, a single RF channel is used, and each handset transmits and receives data during a dedicated time slice or slot within an overall cycle or epoch. Efficient power use is important for a wireless system since the handsets are typically battery-powered. The base unit typically requires more power to operate than the handsets, and is thus usually powered by an external AC power supply.

Irregularities may occur in the AC power, such as a loss of power or momentary power spikes or glitches, which can cause communications to be disrupted. For example a power glitch may cause a loss of TDMA synchronization.

5

### SUMMARY

A wireless telephone system comprises one or more wireless handsets and a base unit. Each handset has a handset transceiver and a rechargeable handset battery for powering the handset. The base  
10 unit has a base transceiver for communicating over an RF channel with each handset via its handset transceiver; a recharge cradle for physically docking a docked handset battery comprising one of a detached handset battery and a handset; and a recharge unit for recharging the docked handset battery. The base unit is coupled to an  
15 AC power supply and utilizes the docked handset battery as a backup power supply if AC power from the AC power supply is lost or irregular to prevent communication between the base unit and the handsets from being disrupted.

20

### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of TDMA multi-line wireless telephone system, in accordance with an embodiment of the present invention.

### DESCRIPTION OF THE PREFERRED EMBODIMENT

25

Referring now to Fig. 1, there is shown a block diagram of spread spectrum TDMA multi-line digital wireless telephone system 100, in accordance with an embodiment of the present invention. TDMA system 100 comprises a base unit 110, which has receiver and transmitter units 112 and 111, respectively, and is coupled to

external telephone network 116 via telephone line(s) 115. Base unit 110 is normally powered by AC power supply 130. Base unit 110 also comprises recharge unit 117, and recharge cradle 118, which is a port or docking station for receiving either a wireless handset having a battery 119, or a detached handset battery 119. Recharge unit 117 is driven by AC power in and provides DC power to power base unit 110 and/or to recharge any battery 119 placed in cradle 118 via contacts provided in cradle 118 which electrically couple with contacts in either the docked handset or on the docked battery 119 itself.

System 100 also comprises N wireless handsets  $120_1, 120_2, \dots, 120_N$ . Each has a transmitter and receiver unit (transceiver), such as transmitter 121 and receiver 122 of handset  $120_1$ . Each handset also comprises a rechargeable battery 123. In one embodiment, receiver unit 112 comprises N logical receivers, and transmitter unit 111 comprises N logical transmitters, so that receiver and transmitter units 112 and 111 provide N logical transceiver units, one for each of N wireless handsets. At any given time, M handsets ( $0 \leq M \leq N$ ) are operating or active (i.e., in the process of conducting a telephone call).

The telephone system provided by system 100 preferably operates in the 900 MHz unlicensed band, and preferably provides features like that of a small PBX, in conjunction with PC 140. In one embodiment, system 100 employs a combination of time division multiplexing (TDM), such as TDMA, and frequency band selection to overcome interfering sources and to maintain reliable links between the base-station and the handsets. In a digital TDMA scheme, each handset only transmits or receives data during its own "time slice" or slot. System 100 thus provides a wireless network between the base

station 110 and each handset  $120_i$  ( $1 \leq i \leq N$ ). In one embodiment,  $N=4$ , so that system 100 comprises a maximum of 4 wireless handsets, each having unique time slots in the TDMA epoch dedicated thereto.

As explained above, it is undesirable for communications to be disrupted if the power provided to base unit 110 by AC power supply 130 is lost or has momentary glitches or other irregularities. In the present invention, therefore, base unit 110 is configured to draw power from DC supply 119 as a backup supply in the event that AC power is irregular or lost.

Often there is a battery 119 physically docked in cradle 118, which is either fully recharged or in the process of being recharged. For example, a detached or solo battery may have been placed in cradle 118 previously by a user to charge up an extra handset battery. The detached battery may be used by recharging the battery, and then ejecting a spent battery in a given handset and replacing it with the recharged handset battery; at this point, the spent detached handset battery may be recharged. Alternatively, one of handsets  $120_i$  may not be in use and may have been placed in cradle 118. Whether a detached handset battery is directly docked in cradle 118 or a handset having a battery is docked in cradle 118, cradle 118 contains a docked handset battery 119. For this reason, at any given moment, there may be a battery 119 docked in cradle 118 that has a charge sufficient to power base unit 110 for some length of time. Therefore, in one embodiment, base unit 110 is configured to draw power from a battery 119 in its recharge cradle 118, if the battery is present and has a minimum charge, and if there is a loss of or irregularity in AC power provided to base unit 110.

For example, handset  $120_i$  may be docked with a fully charged battery 123 (also battery 119) in cradle 118, and not in use.

Handsets 120<sub>2</sub> and 120<sub>3</sub> may be engaged in TDMA communication with base unit 110. If an AC power glitch or power loss is detected by base unit 110, base unit 110 draws DC power from battery 119 (i.e., battery 123 of docked handset 120<sub>1</sub>). This allows  
5 communications with handsets 120<sub>2</sub> and 120<sub>3</sub> to continue uninterrupted and to ride out momentary AC power glitches or losses, unless AC power loss is not restored before battery 119 is drained by the relatively heavy power use of base unit 110. In addition, the backup battery power provided in this manner is "free" since no separate  
10 battery dedicated to charging only the base unit is necessary, and the base unit 110 takes advantage of an available recharged battery that is not currently being used by a handset and that would otherwise go to waste without the power backup technique of the present invention. As will be appreciated, if there is no battery 119 docked in  
15 cradle 118 (or if any battery docked therein is not sufficiently charged to power base unit 110), then communications would be disrupted if AC power is lost or irregular. Thus, the base unit power backup feature of the present invention is preferably optional and is made functional only when a sufficiently charged battery 119 is  
20 detected in cradle 118.

In one embodiment, as soon base unit 110 detects that AC power is lost and begins to draw on DC power from battery 119, a signal is sent to all handsets (or all off hook handsets) to notify them that the base unit has experienced AC power failure and is in backup  
25 mode. This can alert any user to investigate AC power failure and to restore it if possible, and also to alert users that communication may soon be lost if the backup power is drained before AC power is restored.

In another embodiment, base unit 110 comprises a locking mechanism designed to make removal of battery 119 more difficult or impossible whenever base unit 110 is in backup mode. This will prevent a user from accidentally removing battery 119 and thus depriving base unit 110 of operating power, when AC power has failed. For example, in normal operation, a user is free to manually insert or remove a battery 119 or handset having battery 119 into or out of cradle 118. In one embodiment, cradle 118 comprises a solenoid-actuated locking mechanism that activates only when base unit 110 enters backup mode, which prevents manual removal of battery 119 unless the user depresses an unlocking switch. This allows a user to remove a battery 119 if necessary, but causes the user to consider whether to do so since the user must depress the unlock switch first.

In a system having only a single handset, if the handset itself is docked in cradle 118, then there may be no need to use its battery as a back up since there is no communication in progress while the handset is being recharged. Conversely, when the handset is engaged in communication with the base unit, it is not docked in the recharge cradle 118 so its battery cannot be used for backup purposes. However, in the case where a solo battery 119 is being recharged in recharge cradle 118 (e.g., an extra battery for the handset), then base unit 110 may resort to battery backup to prevent disruption of communication with the single handset.

In an alternative embodiment, battery 119 is not one of the handset batteries but is a base unit rechargeable battery dedicated solely to provide backup battery power to base unit 110. In this embodiment, battery 119 may be recharged as long as there is AC power, by the same recharging unit 117 that recharges handset



batteries when handsets are docked in cradle 118. In this case, battery 119 may be larger in power storage capacity than the typical batteries employed in handsets 120, to account for the fact that base unit 110 has a much higher power consumption than handsets.

5 In an alternative embodiment, base unit 110 comprises multiple cradles identical to cradle 118, so that more than one handset or solo batter may be recharged at a time.

10 It will be understood that various changes in the details, materials, and arrangements of the parts which have been described and illustrated above in order to explain the nature of this invention may be made by those skilled in the art without departing from the principle and scope of the invention as recited in the following claims.

CLAIMS

1. A wireless telephone system, comprising:
  - (a) one or more wireless handsets, each handset having a rechargeable handset battery for powering the handset;  
5 and
  - (b) a base unit coupled to a source of AC power and comprising a recharge cradle for physically docking a docked handset battery for recharging the docked handset battery, and for providing power from the docked handset battery to the  
10 base unit in response to an irregularity in the AC power.
2. The system of claim 1, wherein the one or more wireless handsets comprises a plurality of wireless handsets.
- 15 3. The system of claim 2, wherein the base unit establishes a time-division multiple access (TDMA) link with each handset via the handset transceiver in accordance with a TDMA epoch allocating exclusive audio packet time slots to each handset.
- 20 4. The system of claim 2, wherein, if the base unit utilizes the docked handset battery as a backup power supply then the base unit transmits a signal to the handsets for notifying the handsets that an irregularity in the AC power has been detected.
- 25 5. The system of claim 1, wherein the one or more wireless handsets comprises a single handset and the docked handset battery comprises a detached handset battery.

6. The system of claim 1, wherein the base unit comprises a plurality of recharge cradles.

7. The system of claim 1, wherein, if the base unit utilizes the  
5 docked handset battery as a backup power supply then the base unit activates a locking mechanism in the recharge cradle that hinders removal of the docked handset battery from the recharge cradle.

8. In a base unit of a wireless telephone system having the  
10 base unit and one or more wireless handsets, the base unit comprising a base transceiver, a recharge cradle, and a recharge unit, each handset comprising a handset transceiver and a rechargeable handset battery for powering the handset, a method comprising the steps of:

- 15 (a) communicating with each handset via the base transceiver and the handset transceiver;
- (b) physically docking with the recharge cradle a docked handset battery comprising one of a detached handset battery and a handset;
- (c) recharging the docked handset battery with the recharge  
20 unit, wherein the base unit is coupleable to a source of AC power;
- (d) detecting an irregularity in the AC power; and
- (e) utilizing the docked handset battery as a backup power  
supply in response to detection of an irregularity.

25

9. The method of claim 8, wherein the one or more wireless handsets comprises a plurality of wireless handsets.

10

10. The method of claim 9, wherein the base transceiver establishes a time-division multiple access (TDMA) link with each handset via the handset transceiver in accordance with a TDMA epoch allocating exclusive audio packet time slots to each handset.

5

11. The method of claim 9, wherein, if the base unit utilizes the docked handset battery as a backup power supply then the base unit transmits a notification signal to the handsets.

10

12. The method of claim 9, wherein the one or more wireless handsets comprises a single handset and the docked handset battery comprises a detached handset battery.

15

13. The method of claim 9, wherein the base unit comprises a plurality of recharge cradles.

20

14. The method of claim 8, wherein, if the base unit utilizes the docked handset battery as a backup power supply then the base unit activates a locking mechanism in the recharge cradle that hinders removal of the docked handset battery from the recharge cradle.

15. A base unit for communicating with one or more wireless handsets, each handset comprising a handset transceiver and a rechargeable handset battery for powering the handset, the base unit

5 comprising:

(a) a base transceiver for communicating over an RF channel with each handset via its handset transceiver;

(b) a recharge cradle for physically docking a docked handset battery comprising one of a detached handset battery and a handset; and

10

(c) a recharge unit for recharging the docked handset battery, wherein the base unit is coupleable to an AC power supply and utilizes the docked handset battery as a backup power supply if AC power from the AC power supply is irregular.

15

16. The base unit of claim 15, wherein the one or more wireless handsets comprises a plurality of wireless handsets.

20

17. The base unit of claim 16, wherein the base transceiver establishes a time-division multiple access (TDMA) link with each handset via the handset transceiver in accordance with a TDMA epoch allocating exclusive audio packet time slots to each handset.

25

18. The base unit of claim 16, wherein, if the base unit utilizes the docked handset battery as a backup power supply then the base unit transmits a signal to the handsets to so notify the handsets.

19. The base unit of claim 15, wherein the one or more wireless handsets comprises a single handset and the docked handset battery comprises a detached handset battery.

5        20. The base unit of claim 15, further comprising a plurality of recharge cradles.

1/1




FIG. 1

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/18106

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 H04M1/72

According to International Patent Classification(IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04M H04B H02J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	GB 2 279 827 A (VTECH COMMUNICATIONS LTD) 11 January 1995 see abstract  see page 6, line 3 - line 10 see page 2, line 22 - line 33 see figure 4 see figure 3	1,5,8, 15,19 2,6,7,9, 14,16,20

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

23 November 1998

Date of mailing of the international search report

01/12/1998

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Lindhardt, U



**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International Application No  
**PCT/US 98/18106**

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
---	---------------------	----------------------------	---------------------

GB 2279827	A	11-01-1995	CA 2124885 A	03-12-1994
			US 5578875 A	26-11-1996

---